

## SERIES GHJ

The Dip hatch main function is to allow easy access to storage tanks while controlling vapor losses. Lecore Dip Hatches are supplied with "O" ring seats in nitrile rubber for easy maintenance.

### FLANGES

Flanges are made to standard ANSI 150 FF. Others available on request.

### CONSTRUCTION

1. Castings in aluminum LM4 or cast iron.
2. "O" ring seat in nitrile rubber.
3. Lockable hand nuts for security.
4. Designed and manufactured to A.P.I. standards.



Normal Size	O/A Dim. in mm. L x H x W	Cat Ref.	Net mass in kg.
3"	220 170 190	GHL/3	3.5
4"	240 165 230	GHL/4	4
6"	330 190 280	GHL/6	8
8"	410 235 345	GHL/8	12

FLANGED TO ASA 150 FF

## SERIES GHV

The Lecore Gauge hatch could be preset to allow pressure relief according to clients' specifications while also allowing easy access into the storage tank.

### SIZES

Available in 6", 8"

### CONSTRUCTION

1. Standard in Aluminum, cast iron and other materials available on request.
2. "O" ring seat in nitrile rubber.

Normal Size	O/A Dim. in mm. L x H x W	Cat Ref.	Net mass in kg.
8"	390 190 172 Rad.	GHL/8	9

FLANGED TO ASA 150 FF

